



## Technical Data Sheet (Mirror)

**Packaging:** Wooden case.

### Product information:

Thickness	3 mm
Thickness tolerance	+/-0.2
Size	2600x1600
Glass type	Mirror (MRO)
Glass Standard	EN
Appearance	Silver Mirror

### Physical Properties:

Silver Layer Thickness	Light Reflectance(%)	Paint Coating Thickness	Paint Adhesion
700mg/m <sup>2</sup>	>83%	Min 45 Micron	Max Grade 2

### Durability:

Resistance to Corrosion		Resistance to Humidity	
Edge Corrosion	After 240hrs. <2.5mm	Edge Corrosion	After 480 hrs. < 0.2 mm
Number of Spots	After 240hrs. 2 of diameter > 0.3mm &< 3mm. 3 of diameter <0.3mm.	Number of Spots	After 480hrs. 1 of diameter <0.3mm



The products in this publication are sold subject to UFG standard terms and conditions of sale and any applicable written warranties will be provided by UFG representative if requested. It is the responsibility of the purchaser to confirm that the products are suitable for their intended application in compliance with the applicable laws and regulations. The performance values shown are nominal and subject to variations due to manufacturing tolerances. A slight shift in visible light reflectance or transmission may be noticed after heat- treatment. Please contact UFG representative to obtain any applicable handling or safety guides and for the most current product information.